



SSD202D
INTR_CPUI NT Module Description

SigmaStar Confidential
for
Internal Use Only
深圳百问网络科技有限公司



SigmaStar Confidential
for
Internal Use Only
深圳百问网络科技有限公司

© 2022 SigmaStar Technology Corp. All rights reserved.

SigmaStar Technology makes no representations or warranties including, for example but not limited to, warranties of merchantability, fitness for a particular purpose, non-infringement of any intellectual property right or the accuracy or completeness of this document, and reserves the right to make changes without further notice to any products herein to improve reliability, function or design. No responsibility is assumed by SigmaStar Technology arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

SigmaStar is a trademark of SigmaStar Technology Corp. Other trademarks or names herein are only for identification purposes only and owned by their respective owners.

1. REGISTER DESCRIPTION

1.1. INTR_CPUINT Register (Bank = 1008)

INTR_CPUINT Register (Bank = 1008)				
Index (Absolute)	Mnemonic	Bit	Description	
20h (100840h)	REG100840	7:0	Default : 0x00	Access : R/W
	-	7:3	Reserved.	
	HST0TO3_INT	2	Host0 to Host3 interrupt.	
	HST0TO2_INT	1	Host0 to Host2 interrupt.	
	HST0TO1_INT	0	Host0 to Host1 interrupt.	
22h (100844h)	REG100844	7:0	Default : 0x00	Access : R/W
	-	7:3	Reserved.	
	HST1TO3_INT	2	Host1 to Host3 interrupt.	
	HST1TO2_INT	1	Host1 to Host2 interrupt.	
	HST1TO0_INT	0	Host1 to Host0 interrupt.	
24h (100848h)	REG100848	7:0	Default : 0x00	Access : R/W
	-	7:3	Reserved.	
	HST2TO3_INT	2	Host2 to Host3 interrupt.	
	HST2TO1_INT	1	Host2 to Host1 interrupt.	
	HST2TO0_INT	0	Host2 to Host0 interrupt.	
26h (10084Ch)	REG10084C	7:0	Default : 0x00	Access : R/W
	-	7:3	Reserved.	
	HST3TO2_INT	2	Host3 to Host2 interrupt.	
	HST3TO1_INT	1	Host3 to Host1 interrupt.	
	HST3TO0_INT	0	Host3 to Host0 interrupt.	
28h (100850h)	REG100850	7:0	Default : 0x00	Access : RO
	HST0_FIQ_STATUS_GROUP [7:0]	7:0	Bit0 => OR (Host0 FIQ final status[7:0]). Bit1 => OR (Host0 FIQ final status[15:8]). Bit7 => OR (Host0 FIQ final status[63: 56]).	
28h (100851h)	REG100851	7:0	Default : 0x00	Access : RO
	HST0_IRQ_STATUS_GROUP [7:0]	7:0	Bit0 => OR (Host0 IRQ final status[7:0]). Bit1 => OR (Host0 IRQ final status[15:8]).	

INTR_CPUINT Register (Bank = 1008)				
Index (Absolute)	Mnemonic	Bit	Description	
		 Bit7 => OR (Host0 IRQ final status[63: 56]).	
29h (100852h)	REG100852	7:0	Default : 0x00	Access : RO
	HST1_FIQ_STATUS_GROUP [7:0]	7:0	Bit0 => OR (Host1 FIQ final status[7:0]). Bit1 => OR (Host1 FIQ final status[15:8]). Bit7 => OR (Host1 FIQ final status[63: 56]).	
29h (100853h)	REG100853	7:0	Default : 0x00	Access : RO
	HST1_IRQ_STATUS_GROUP [7:0]	7:0	Bit0 => OR (Host1 IRQ final status[7:0]). Bit1 => OR (Host1 IRQ final status[15:8]). Bit7 => OR (Host1 IRQ final status[63: 56]).	
2Ah (100854h)	REG100854	7:0	Default : 0x00	Access : RO
	HST2_FIQ_STATUS_GROUP [7:0]	7:0	Bit0 => OR (Host2 FIQ final status[7:0]). Bit1 => OR (Host2 FIQ final status[15:8]). Bit7 => OR (Host2 FIQ final status[63: 56]).	
2Ah (100855h)	REG100855	7:0	Default : 0x00	Access : RO
	HST2_IRQ_STATUS_GROUP [7:0]	7:0	Bit0 => OR (Host2 IRQ final status[7:0]). Bit1 => OR (Host2 IRQ final status[15:8]). Bit7 => OR (Host2 IRQ final status[63: 56]).	
2Bh (100856h)	REG100856	7:0	Default : 0x00	Access : RO
	HST3_FIQ_STATUS_GROUP [7:0]	7:0	Bit0 => OR (Host3 FIQ final status[7:0]). Bit1 => OR (Host3 FIQ final status[15:8]). Bit7 => OR (Host3 FIQ final status[63: 56]).	
2Bh (100857h)	REG100857	7:0	Default : 0x00	Access : RO
	HST3_IRQ_STATUS_GROUP [7:0]	7:0	Bit0 => OR (Host3 IRQ final status[7:0]). Bit1 => OR (Host3 IRQ final status[15:8]). Bit7 => OR (Host3 IRQ final status[63: 56]).	